Technical Sheet

FSG

Skruer med flat hode til gipsplater

The wafer head screw for plasterboard is used for fixing lighter fittings such as picture hooks and towel rails directly into plaster, without a batten base. When fixing use a screwdriver, not a power screwdriver, due to the risk of over torque.



INDOOR

EG





Features

Features

- Krysspunktdrift.
- Wafer hode.
- Skarp spiss.
- Grov gjeng.
- Elektrogalvanisert belegg.

Applications

Suitable for

- Lysarmaturer til gipsplater.
- Håndklestativ til gipsplater.
- Generelle, lette oppheng.

FSG
Skruer med flat hode til gipsplater

Teknisk data



Dimensjoner

Referanse	Fasteners dimensjoner									
	Item Code	annet				produktdimensjoner[mm]				
		DB nr.	NOB nr.	antall per eske	vekt[kg]	D[mm]	L[mm]	d_h[mm]	d1[mm]	bit[mm]
FSG4.8X25	74400	1949895	53293172	250	0.002	4.8	28	9	3	PH2
FSG4.8X35	74401	1949896	53293183	250	0.003	4.8	38	9	3	PH2

Simpson Strong-Tie c/o Christiania Spigerverk
Smalvollveien 58, 0667 Oslo
22021300
kundeservice@spigerverket.no

Copyright by Simpson Strong-Tie®
Informasjonen i dette dokumentet eies eksklusivt av Simpson Strong-Tie. De er kun gyldige i forbindelse med produkter solgt av Simpson Strong-Tie.